

日期/Date		档案员 Filing Clerk		1		2		3		4		5		6	
技术参数: 产品系列: M12 D-code 插针数: 4 额定电流(40℃): 4A 额定电压: 250V 额定脉冲电压: 2500V 污染等级: 3 接触电阻: ≤10mΩ 绝缘电阻: ≥100MΩ 锁紧方式: 螺纹式M12*1 电缆类型: PUR, 清水蓝 RAL5021 线规: 0.14mm² (AWG26) 防护等级: IP67 插拔次数: ≥100 温度范围: -25℃ ... +85℃ 外壳材料: TPU 插体材料: PA 插针材料: 铜合金 插针电镀材料: 金 Technical specification: Series: M12 D-Code Number of contacts: 4 Rated current (40℃): 4A Rated voltage: 250V Rated impulse voltage: 2500V Pollution degree: 3 Contact resistance: ≤10mΩ Insulation resistance: ≥100MΩ Connector locking system: screw M12*1 Cable type: PUR , Clear blue RAL 5021 Wire gauge: 0.14mm² (AWG26) Degree of protection: IP67 Mating cycles: ≥100 Temperature range: -25℃ ... +85℃ Material of housing: TPU Material of insert: PA Material of contact: copper alloy Contact plating: Au															

例如型号”M12-M04D-T/F04D-T-L-PUR-Cat.5e”,
”L”表示带线长度, 单位m。
Ex: Part code”M12-M04D-T/F04D-T-L-PUR-Cat.5e”,
the ”L” represents the cable length, unit m.